

Product information

Index	13.5502.9113.63
Category	Exit signage
Family	Brick SN

Light and electrical features


Light source	LED
Self-test	Yes
Colour temperature [K]	5000
Operating temperature	5°C to 40°C
Voltage	220...240V, 50...60 Hz
Degree of insulation	Class 2
Number of LEDs	4
Visual indications (LED colour)	Green
Glow wire test	850°C
Type	Maintained
Real power of luminaire [W]	1.79
Lifetime of LED sources [h]	50000
Real luminous flux [lm]	150

Battery

Autonomy [h]	1
Battery type	Ni-Cd
Capacity	0,8Ah
Battery voltage	3,6V

Mechanical features

Material	Polycarbonate
Ingress protection degree (IP)	43
Impact protection (IK)	5
Installation	ceiling surface
Colour	white RAL 9003
Dimensions A x B x H [mm]	165 x 202 x 45
Weight [kg]	0.36



Stylized design of pure and essential lines. Its small size and geometric characteristics provide the necessary security with the least possible visual impact. Suitable for wall mounting with horizontal or vertical emission using its accessories. Intelligent self-test system for the correct maintenance of the batteries, prevention and detection of failures. The Brick version combines security with a minimalist design. With this version it reaches a vision of 24 meters according to UNE-EN1838.

Consult us for custom made versions.

