

Product information

| | |
|----------|-----------------|
| Index | 13.5502.9212.63 |
| Category | Exit signage |
| Family | Brick SN |

Light and electrical features


| | |
|---------------------------------|------------------------|
| Light source | LED |
| Self-test | Yes |
| Colour temperature [K] | 5000 |
| Operating temperature | 5°C to 40°C |
| Voltage | 220...240V, 50...60 Hz |
| Degree of insulation | Class 2 |
| Visual indications (LED colour) | Green |
| Glow wire test | 850°C |
| Type | Maintained |
| Lifetime of LED sources [h] | 50000 |
| Real power of luminaire [W] | 2.51 |
| Real luminous flux [lm] | 300 |
| Number of LEDs | 8 |

Battery

| | |
|-----------------|-------|
| Autonomy [h] | 1 |
| Battery type | Ni-Cd |
| Battery voltage | 3,6V |
| Capacity | 1,6Ah |

Mechanical features

| | |
|--------------------------------|-----------------|
| Material | Polycarbonate |
| Ingress protection degree (IP) | 43 |
| Impact protection (IK) | 5 |
| Installation | ceiling surface |
| Colour | white RAL 9003 |
| Dimensions A x B x H [mm] | 165 x 202 x 45 |
| Weight [kg] | 0.419 |



Stylized design of pure and essential lines. Its small size and geometric characteristics provide the necessary security with the least possible visual impact. Suitable for wall mounting with horizontal or vertical emission using its accessories. Intelligent self-test system for the correct maintenance of the batteries, prevention and detection of failures. The Brick version combines security with a minimalist design. With this version it reaches a vision of 24 meters according to UNE-EN1838.

Consult us for custom made versions.

